



# DOUBLE WALL TRAILERS

990 GALLONS



## FULLY COMPLIANT FOR BULK DIESEL

Thunder Creek's Double Wall Trailers provide 110% containment with a 990 gallon diesel tank and pumping system mounted in a secondary tank. They are compliant with the EPA's SPCC Program as well as DOT 406 regulations.

Like all Thunder Creek trailers, Double Wall Trailers are built to travel smoothly at highway speeds and stand-up in the toughest environments.

The rear utility box model can be equipped to function as an on-site shop on wheels. Utility Box options include a grease system, a variety of toolboxes and utility appliances such as compressors, generators and welders.

An ISO 22241 Compliant DEF Delivery System can be added in the front enclosure at any time. This system utilizes Thunder Creek's exclusive 2-in-1 DEF Pumping System to handle DEF in a closed path to maintain purity to off-road machines.

**DOT406,  
EPA SPCC,  
TRANSPORT  
CANADA  
COMPLIANT**





# DOUBLE WALL TRAILERS

## FUEL AND SERVICE TRAILERS

**INDUSTRY LEADING  
3 YEAR TANK  
WARRANTY**



Fully Contained Pumping System



Manhole for Tank Inspection



Lift Points

## STANDARD FEATURES

### DUAL WALL DIESEL TANK

- 10 Gauge Steel Tanks
- Lockable Enclosure for Pumps, Vents, Fill Ports
- 2" Roll Bar Around Tank, Vents and Fill Ports
- Tank Bolts to Chassis with Built-In Lift Points
- 110% Fuel Containment
- Outer Tank can be separated for Inspection
- 16" Manhole in Primary Tank for Inspection
- Emergency Shut-Off

### TRAILER

- 7.5" x 1/4" Formed Frame
- Dexter® Torsion Axles and EZ Lube Hubs
- Electric Brakes with Breakaway Safety System
- 16" 10-Ply Tires 235/80R16 with Steel Wheels
- 7,000 lb. Enclosed Jack and Safety Tow Chains
- DOT Placards, Reflective Tape and LED Lights
- Replaceable, Bolt-on Fenders
- Dual Coat Gray Polyurethane Paint
- Replaceable Diamond Plate Rock Guard
- Adjustable Height 2 5/16" Ball Hitch
- Wiring Wrapped in Protective Braid

### FRONT ENCLOSURE 49 CU. FT

- Positive Pressure Dust Control System
- Automatic Interior LED Lighting
- 12V Deep Cycle Marine Battery
- Lockable Hatch-Style, Weather-Sealed Doors with Chrome Handle
- Fire Extinguisher

### PUMP ENCLOSURE

- Fully Contained Pumping Area
- Lockable Hatch-Style, Weather-Sealed Doors with Chrome Handle
- Automatic Interior LED Lighting
- See Pumping System Options for Fuel Pump Configuration

## OPTIONS

Items with + can be added any time to expand the functionality of the trailer as your operation grows.

### TRAILER OPTIONS

- Aluminum Wheels
- 14-Ply Tires
- Custom Color
- Solar Battery Maintainer +
- WorkSight Light Tower +
- Electric/Hydraulic Jack +
- Spare Tire Kit with Standard or Field Max Tires +
- Stainless Steel Trim + Fender Upgrade
- 100 Gallon DEF Delivery System (details below) +
- 30 Gallon Auxiliary Oil Tank and 3 GPM Pump +
- Gear Drive 8 GPM Pump Upgrade for Oil Tank
- Five Drawer Tool Chest for Front Enclosure +
- Spill Containment Kit +
- Static Discharge Reel +

### PUMPING SYSTEM OPTIONS

- 15 GPM Industrial Grade 12V Pump
- 25 GPM Gas Powered Pump
- Gasoline Pumping System
- 35' x 1" Retracting Hose Reel, Auto-Trip Nozzle (standard with selection of pump)
- 50' x 1" Retracting Hose Reel, Auto-Trip Nozzle
- 10 Micron Fuel Filter (standard with selection of pump)
- 4 Micron Fuel Filter
- Digital Fuel Meter +

### REAR UTILITY BOX OPTIONS\*

- Rear Utility Box (35.5"d x 58.5"w x 47"h)
- Five Drawer Tool Chest for Utility Box +
- Can+Towel Holder +
- Two Drawer Low Boy Tool Chest +
- Work Bench with Vise +
- 35 lb. Grease Kit +
- Welder+Comp+Gen with 50' Air/Elec. Combo Reel +
- Comp+Gen with 50' Air/Elec. Combo Reel +
- 35 CFM Air Compressor with 50' Air Hose Reel +



\*Available on DW990UB model only

### DIESEL EXHAUST FLUID OPTIONS

- DEF Delivery System +
- 100 Gallon HDPE Tank
- Bi-Directional Pump
- 35' Reel
- Digital DEF Meter +
- 50' DEF Hose Reel
- 120V DEF Heater +



## SPECIFICATIONS

Model	DW990 	DW990UB 
Inner Tank	990 gallon   four baffles   10 ga.	990 gallon   four baffles   10 ga.
Outer Tank	1,089 gallon   10 gauge	1,089 gallon   10 gauge
Torsion Axles   Hubs	dual 7,000 lbs.   8 bolt hubs	triple 6,000 lbs.   8 bolt hubs
L   W   H	19"   7'   6'	23'   7'   6'
Empty Weight   GVWR	4,250 lbs.   14,000 lbs.	5,270 lbs.   18,000 lbs.